



Kensington

A robust, lightly textured, plain colour hide. It is suitable for all upholstery applications. Its high flammability and very high performance make it especially suitable for contract environments.

Application Usage

- | | | | | |
|--|---|--|--|---|
| <input type="checkbox"/> Light Domestic | <input type="checkbox"/> Light Contract (Crib 5) | <input checked="" type="checkbox"/> General Marine | <input checked="" type="checkbox"/> General Aviation | <input checked="" type="checkbox"/> After Market Auto |
| <input type="checkbox"/> General Domestic | <input type="checkbox"/> General Contract (Crib 5) | <input type="checkbox"/> Luxury Marine | <input type="checkbox"/> Corporate Aviation | <input type="checkbox"/> Luxury AM Auto |
| <input checked="" type="checkbox"/> Heavy Domestic | <input checked="" type="checkbox"/> Heavy Contract (Crib 5) | <input type="checkbox"/> Aviation Panels | <input checked="" type="checkbox"/> OEM Std Auto | <input type="checkbox"/> OEM Luxury Auto |
| | <input type="checkbox"/> Severe Contract (Crib 7) | | | |

Test Results

Test	Method	Requirement
Substance	BS EN ISO 2589:2002	1.2 - 1.3mm
Fastness to Light	BS EN ISO 105-BO2:1999	Min 5 Blue Scale
Fastness to Rubbing	BS EN 11640/11641:1998	500 Wet/1000 Dry
Flex Endurance	BS EN 5402:2002	100,000
Tear Strength	BS EN 3377-1:2002	40N
Finish Adhesion	ISO 11644:1993	4N
pH (min)	EN ISO 4045:1998	Min 3.2
Water Spotting	ISO 15700:1999	Grade 3 (No Residual Halo)
Cold Crack	EN ISO 17233:2002	-15C
Abrasion Resistance (Taber)	BS EN 14327:2003	CS10/1000 cycles/500g - 4 min
Accelerated Ageing	ISO FDIS 17228	Report Changes
Fastness to Water	BS EN 11642:1998	Grade 4 Min
Domestic FR	BS 8582:1979	Pass
Contract FR	BS 7176 - Crib 5	Pass
Aviation FR	JAR 25.853 a (app F) 1.(1).1	Pass
Marine FR	IMO A.652 (16)	Pass
Auto FR	FM VSS 302:1978	Pass